

## Dobór ramp podjazdowych

		DŁUGOŚĆ RAMPY							
		0,92m	1,20m	1,50m	1,80m	2,10m	2,40m	3,00m	
<b>WZNIESIENIE RAMPY</b>	<b>7,5cm</b>	4,8°	3,6°	2,9°	2,4°	2,0°	1,8°	1,4°	<b>NACHYLENIE RAMPY</b>
	<b>10cm</b>	6,4°	4,8°	3,8°	3,2°	2,7°	2,4°	1,9°	
	<b>12,5cm</b>	8,0°	6,0°	4,8°	4,0°	3,7°	3,0°	2,4°	
	<b>15cm</b>	9,6°	7,2°	5,7°	4,8°	4,1°	3,6°	2,9°	
	<b>17,5cm</b>	11,2°	8,4°	6,7°	5,6°	4,8°	4,2°	3,3°	
	<b>20cm</b>	12,8°	9,6°	7,7°	6,4°	5,5°	4,8°	3,8°	
	<b>22,5cm</b>	14,5°	10,8°	8,6°	7,2°	6,2°	5,4°	4,3°	
	<b>25cm</b>	16,1°	12,0°	9,6°	8,0°	6,8°	6,0°	4,8°	
	<b>30cm</b>		14,5°	11,5°	9,6°	8,2°	7,2°	5,7°	
	<b>35cm</b>			13,5°	11,2°	9,6°	8,4°	6,7°	
	<b>40cm</b>				12,8°	11,0°	9,6°	7,7°	
	<b>45cm</b>				14,5°	12,4°	10,8°	8,6°	
	<b>50cm</b>					13,8°	12,0°	9,6°	
	<b>55cm</b>						13,2°	10,6°	
	<b>60cm</b>						14,5°	11,5°	
	<b>65cm</b>							12,5°	
	<b>70cm</b>							13,5°	
	<b>75cm</b>							14,5°	
	<b>80cm</b>								
<b>85cm</b>									
<b>90cm</b>									

Notatki:

.....

.....

.....

.....

.....

.....